

Zagroda 1801

150 cm Sweeping machine 14 KW Hydraulic drive (Front- rear 3 point hitch, forklift mount)



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/z09-1022>



Parameters

Name	Unit
Working width	1800 mm
Weight	250 kg

Description

STANDARD EQUIPMENT:

- 3-point hitch, front or rear
- Forklift connection (rigid connection)
- Hydraulic drive, (14 kw)
- Brush with a diameter of 510 mm 1 of 3 types (mix type in standard)
 - Brush mix (metal + polypropylene)
 - Brush (Polypropylene)
 - Spiral brush mix for snow
- Two road wheels and one support wheel at the front ø 200x50 with mechanical height adjustment
- Terrain following system in two planes
- Diagonal sweeping position (condition - no dirt tank)
- Mechanical sweeper angle adjustment

OPTIONAL EQUIPMENT:

- Garbage container with mechanical discharge using a cable from the vehicle
- Garbage container with hydraulic dump
- Sprinkler system - consists of: tank with a capacity of 175l with external filter, conveying pump / vehicle powered installation: 12 (24 v), rod with flat nozzles.
- Rotary side brush in three types to choose from: mix, ppn or metal type (can be installed on the right or left side or on both sides), the side brush drive installation is equipped with a shut-off valve

enabling it to be switched off without disassembly

- Other types of brackets for wheel loaders possible
- Hydraulic sweep angle adjustment, allowing sweeping without leaving the vehicle
- Attention !!! additional hydraulic section required
- Pressure relief valve for loaders with a hydraulic pressure greater than 16 mpa
- Oil flow regulator for chargers with a flow rate greater than 60 l / min.
- Reinforced hydraulics for wheel loaders with high oil flow