

Zagroda 2430

Cardan driven concrete mixer (600 L, rear discharge, fork lift mounts)



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/z09-1036>



Parameters

Name	Unit
Capacity (liter)	600 l
Drivegear	tractor PTO
Concrete mixer diameter	1200 mm
Weight	490 kg

Description

STANDARD EQUIPMENT:

- 3-point hitch cat. II
- Additionally adapted for carrying with pallet forks
- Sheet thickness: central element - 5mm; bottom - 8mm for 800l and 1200l, 6mm for 600l
- Mixer arms made of 3 flat springs (600 L), 4 arms (800 L) or 5 arms (1200 L), rotating around 30 r.p.m.
- Working tips of the stirrers with adjustable working height
- Aggregate segregating sieve during filling of the mixer
- Side and rear discharge for 800L and 1200L, rear discharge for 600L
- Metal cover on the tractor side
- In standard version, drive from the tractor via PTO.
- power demand 600L - 60ps, 800L - 80ps, 1200L - 110ps
- 800L concrete mixers for mounting hydraulic motor

OPTIONAL EQUIPMENT:

- Cement mixer with a hydraulic drive.
Recommended oil flow rate: 60-70L / min;
max. should not exceed 80L / min
- PTO version additionally equipped
with hydraulic motor with hoses
- Concrete mixer with electric motor drive (360v),
for concrete mixers 600L and 800L 11kw engine
/ requires protection. 25a /, for concrete mixers
1200L - 15kw engine / requires protection 32a /
- Self-loading shovel - assembly



possible in 800L and 1200L concrete
mixers with side discharge only
• Chassis for concrete mixer 800 L and 1200L
on 260/75 / 15.3 wheels (weight 350kg)
• PTO shaft 460 Nm with overload protection