

AGF-200

Verge mulching mower 200cm

Item no.: J33-10259



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/agf-200-verge-mulching-mower-200cm>



Parameters

Name	Value
Weight	890 kg
RPM	540 rpm
Mowing width	1980 mm

Description

The especially robust construction of the AGF-200 verge mulching mower makes it stand out. In contrast to the lighter models "AGL" this is the heaviest mowing unit model (higher material strength etc.) we are dealing with. Heavier 1.2 kg hammers are also installed in this mowing unit, not the otherwise standard 800 g hammers. The Jansen AGF-200 has a specially strengthened angular gearbox. An improved three-point hanger now provides even more stability. Through lateral alignment of the mowing unit you can mow ditches, bank areas, earth walls, etc., with ease.

Fundamental improvements compared to the previous model:

- wider mulch housing
- massively reinforced and improved three-point hanger
- reinforced trailing roller
- reinforced flail shaft
- stable transport rollers
- improved collision protection

This model has a mowing width of 198 cm and is driven using a P.T.O, included as part of the delivery. It can be moved to the left and right and you can set it at an angle (90° upward and 55° downward). For this function you need 2 hydraulic control circuits on your tractor, as the mower unit has 2 double-action hydraulic cylinders for this purpose.

The 20 specially hardened, 1.2 kg hammer blades, which are arranged on a double spiral drive shaft, shred clippings to a minimum size. Even very high grass, bushy or straw-like clippings are no problem for this mower because 2 counter blades are installed.

With maximum lateral alignment the dimension from the middle of the tractor to the outer edge of the mowing unit is approx. 290 cm.

Furthermore, the Jansen AGF-200 comes with collision protection. This is triggered in the event of contact with hindrances, for example fencepost etc., and allows the verge mulching mower unit to swing upward, side and backward in order to minimise the risk of greater damage.

The cutting height can be set with the top controller and the runners mounted on the side. The AGF-200 mulching mower additionally has a trailing roller and a freewheel gearbox. The suspended, galvanised slats at the front of the mower unit prevent stones escaping. The transport wheels make it easier for you to manoeuvre on level ground without attaching the mower to your tractor.

The mower unit is hung using the three point linkage of your tractor (from Cat. II). Your tractor should have at least 60 HP.

Technical specifications:

Mowing width: approx. 1980 mm

Weight: 890 kg

Tilt movement range: +90° to -55°

Cutting blade type: 1.2 kg hammer blades (20 pc.)

P.T.O: Included in delivery

Rpm: 540

drive shaft Ø: 170 mm

trailing roller Ø: 170 mm

Wall thickness: 4 - 15 mm (depending on location on the mower)

Drive: 5 Piece drive belt

Mounting: Three point hitch from Cat. II

Tractor: min. 60 HP

Dimensions built: approx 2600x2150x1120 mm (LxWxH)

Packaging measurements: 2610x1130x910 (LxWxH)

Weight including packing: 983 kg