


AGF-240

Verge mulching mower 240cm

Item no.: J33-10261



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/agf-240-verge-mulching-mower-240cm>



Parameters

Name	Value
Weight	930 kg
RPM	540 rpm
Mowing width	2390 mm

Description

The especially robust construction of the AGF-240 verge mulching mower makes it stand out. In contrast to the lighter models "AGL" this is the heaviest mowing unit model (higher material strength etc.) we are dealing with. An improved three-point hanger now provides even more stability. Heavier 1.2 kg hammers are also installed in this mowing unit, not the otherwise standard 800 g hammers. The Jansen AGF-240 has a specially strengthened angular gearbox. Through lateral alignment of the mowing unit you can mow ditches, bank areas, earth walls, etc., with ease. vFundamental improvements compared to the previous model:

- wider mulch housing
- massively reinforced and improved three-point hanger
- reinforced trailing roller
- reinforced flail shaft
- stable transport rollers
- improved collision protection

This model has a mowing width of 239 cm and is driven using a P.T.O, included as part of the delivery. It can be moved to the left and right and you can set it at an angle (90° upward and 55° downward). For this function you need 2 hydraulic control circuits on your tractor, as the mower unit has 2 double-action hydraulic cylinders for this purpose.

The 24 specially hardened, 1.2 kg hammer blades, which are arranged on a double spiral drive shaft, shred clippings to a minimum size. Even very high grass, bushy or straw-like clippings are no problem for this mower because 2 counter blades are installed.

With maximum lateral alignment the dimension from the middle of the tractor to the outer edge of the mowing unit is approx. 329 cm.

Furthermore, the Jansen AGF-240 comes with collision protection. This is triggered in the event of contact with hindrances, for example fencepost etc., and allows the verge mulching mower unit to swing upward, side and backward in order to minimise the risk of greater damage.

The cutting height can be set with the top controller and the runners mounted on the side. The AGF-240 mulching mower additionally has a trailing roller and a freewheel gearbox. The suspended slats at the front of the mower unit prevent stones escaping. The transport wheels make it easier for you to manoeuvre on level ground without attaching the mower to your tractor.

The mower unit is hung using the three point linkage of your tractor (from Cat. II). Your tractor should have at least 90 HP.

Technical specifications:

Mowing width: 2390 mm

Weight: ca. 930 kg

Tilt movement range: +90° to -55°

Cutting blade type: 1.2 kg hammer blades

P.T.O: Included in delivery

Rpm: 540

drive shaft Ø: 170 mm

trailing roller Ø: 170 mm

Wall thickness: 4 - 15 mm (depending on location on the mower)

Drive: 5 Piece drive belt

Mounting: Three point hitch from Cat. II

Tractor: min. 90 HP

Packaging measurements: 2990x1130x900 mm (LxWxH)

Weight including packing: 1.050 kg