

Alpha M 2200 (used A1-31808)

2.2 m horizontal shaft stalk crusher

Item no.: A1-31808



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/alpha-m-2200-used-a1-31808-22-m-horizontal-shaft-stalk-crusher>



Parameters

Name	Value
Weight	422 kg
Working width	2200 mm
RPM	540 rpm
Hammer PCs	36 pcs
Sparepart Weight	700 g
Minimum HP	45 hp
CAT	I, II
V-Belts	4 pcs
Rotor Diameter	112 mm
Total diameter	352 mm
Width	2380 mm
Length	790 mm
Height	900 mm
Sideshift movement to the left	800 mm
Sideshift movement to the right	1400 mm
Drivegear	tractor PTO
Max tree diameter	3-4 cm

Description

Description: Used stalk crusher/mulcher Year of manufacture: 2022 Offer conditions and viewing: The equipment can be viewed and tested at our premises at a pre-arranged time. Being a used machine, the price refers to the current aesthetic condition, which can be seen in the pictures. The machine is technically fully operational and can be put to work immediately, however, signs of regular use (surface paint wear, scratches on the frame structure, and traces of gravel impact in the crushing chamber) are visible on it. These aesthetic defects do not affect the structural integrity and excellent performance of the machine. The following equipment / parts / components are missing and defective from the machine: - Machine housing cracked on both sides - Rear door deformed, but still functions (more of an aesthetic defect) - Rear roller scraper - Scraper holder tab broken Specifications of a new, factory machine: - Working width: 220 cm - Horsepower requirement: 45 hp - Cat I-II. 3-point suspension - Weight: 422 kg - Belt: 4 V-belts - Can be operated with a 540 rpm PTO drive - Hammers: 36 pcs (750 g/pc) which are arranged in 2 rows in a spiral shape - Rear door that can be opened and fixed in several positions - Adjustable height skid plate and smoothing roller - Roller scraper - Equipped with SKF bearings - Mounting: machine slightly offset from the center, in order to reach under as much wood as possible - Strong, robust gear unit and structure