



Intermac ASF700

Front and rear mountable blower with 180° rotation of air outlet (366 m³/min)



Parameters

Name	Unit
Weight	415 kg
Minimum HP	80 hp
CAT	II
Blade	10+10 pcs
Turbine	70 cm
RPM	540 rpm
Airflow	22000 m ³ /h
Dimensions	1500 x 1200 x 1400 mm
Drivegear	Tractor PTO
Air speed	250 km/h

Description

Professional high performance blowers

Blowers with high speed and high air flow rate ejected for superior work performance! Perfect for cleaning parks, boulevards, golf courses, roads, large areas with light and medium-heavy bodies, to dry wet roads in the presence of water stagnation in the slight hollows of the asphalt. To improve the working conditions, the air discharge performs a 180° rotation and an adjustment of the opening that can vary its inclination. The blower on two pivoting wheels, which can be adjusted for one constant working height.

- impeller diameter Ø cm 70
- N° blade 10+10
- Gear box for P.T.O./ rpm 540/1000
- Mounted front or back to the hydraulic lifting cat. 2^
- Maximum quantity of ejected air mc/h 22000
- Maximum speed of ejected air Km/h 250
- Minimum power of tractor HP 80/100
- Dimension W x L x H cm 120x150x140
- Weight KG 415

Front application or back.

Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/i10-0948>

