

Intermac BAF120

120 cm front mounted suction mouth for suction systems



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/i10-0900>



Parameters

Name	Unit
Working width	1200 mm
Weight	70 kg
Drivegear	hydraulic engine

Description

The suction and exhaust tube is not a standard accessory.

Front suction point

The Intermac BAF120 suction nozzle with hydraulically driven sweeping brush has an oil consumption of only 8 - 16 L/min. The suction power should be provided by an external suction unit.

- Working width 120 cm
- Hydraulically driven Nylon brushes type 2
- Hydraulic motor displacement 40 cc
- Hydraulic motor speed min. 200 to max. 400 rpm
- Required oil flow min. 8 to max. 16 L/min
- Suction tube diameter $\varnothing$ 200 mm
- 1 Piece height adjustable front swivel wheel $\varnothing$ 280 mm
- 2 Height adjustable rear swivel wheels $\varnothing$ 150 mm
- Adjustable front opening
- Floating movement
- Prepared for mounting side brushes diameter $\varnothing$ 55 cm
- Dimensions WxDxH 130 x 90 x 80 cm
- weight 70 kg