

BedFormerTD45-185

Bed Former 185 cm

Item no.: F41-4978



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/bedformertd45-185-bed-former-185-cm>



Parameters

Name	Value
Company	Forigo

Description

Machines high specialized in the bed forming process for the horticultural sector, which we advise to use in not very stony soil. Bed former series are projected with a front deep tilling rotor fitted with knives and a rear counter rotating rotor, which crumble and shapes the bed. The series include single, double, triple, fixed as well as folding machine available in various working widths (90-600 cm) and suitable from 40 to 400 HP tractors. Effective soil refinement at various working depth, high forwarding speed, high work performance with very damp soil: here some benefits of our Bed formers. Universal 3 point linkage Cat. 2 & 3, Tractor linkage swinging arms, Single speed gearbox 1000 rpm PTO, Central standard Cardan shaft (1"3/8 Z=6 tractor side yoke), Lateral Cardan shaft s with automatic clutch SC, Central machine joint with automatic limiter SC, Pair of front adjustable lateral discs adjustable in, width and height Ø 460 mm, Pair of middle ploughshares adjustable in height and width, Swinging and side adjustable machines supports, Bases and joints for machines linkage, Pair of supporting rear wheels for central machine, Hydraulic system for opening and refolding, Hydraulic locking system for transport position, 225 cm wide during transport, Rear lights bar. 3x Independent Bed Formers which can be used individually Machines equipment: Universal 3 point linkage Cat. 2, Single speed gearbox 540 rpm PTO, Rear PTO connection, Front tilling rotor Ø490 mm mm, Tilling rotor transmission chain in oil bath, Rear crumbling rotor Ø360 mm with high, resistance and wearing steel spikes, Rear rotor transmission chain in oil bath, Front dual metal face seals in oil bath on rotors, Removable flanged rotors, Automatic chain tensioner on spring, 4x blades per flange, length 300 mm, Rear adjustable hood, Working depth adjustable by crank handles, Pair of wearing round rod on side pannels.