AgroHof.com

DFF-GREEN 300

3 m finishing mower (2 rotor)

Item no.: B15-1702

Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

https://agrohof.com/product/dff-green-300-3-m-finishing-mower-2-rotor

Parameters

Name	Value
Working width	3000 mm
Weight	1050 kg
Minimum HP	70 hp
Number of Y knife	4 pcs

Description

Made of high quality materials and with working widths of 1.5m-2.7m, DFF-Green finishing mower are suitable for tractors from 90 HP. Up to 130 hp. Interchangeable chain or blade cutting tools. High working speed and extra-fine cutting system. The finishing mower are equipped with knives that are interchangeable or with 16 mm chains. The same systems of blade holder and/or chain holder allow to work with 2 or 4 blades or chains to improve the shredding of the waste. The transmission or cardan shaft is equipped with a safety clutch to the discs. These models are manufactured in widths of 3 metres in the DFF-300 Green model and are equipped with a folding system for passages between rows and fields of different working sizes in the DFF-Green models 3.10 m - 3.60 m and 5.50 m. As an option, the 3 and 3.10 metre models can be fitted with a hydraulic disc or wheel that can also be used to edge the contour of the tree trunk by cutting the surrounding grass in organic farming systems. The ground supports on this model of maintenance brushcutters are provided with skids lined in their friction parts with treated steel and as an option they allow for rear rollers or solid rubber wheels. It can be used for maintenance of pastures, agricultural areas, airports, forest areas, micro forest treatments, gardening and green spaces in general.

As standard:

-Height regulation by means of skids.
-Double mesh front chains.
-Rubber flaps for integral protection.
-Rear rubber support wheels.
-CAT-III hook.
-Side folding cylinders in models from 310 cm.
-Mobile blade holder and propeller blades.
-Perfect cut overlap.
-Transmission with safety clutch.