

AARDENBURG Disc Mower 500 Cylinder

50 cm hydraulically driven, skid-mounted side mower with hydraulic intercept system



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/a01-5276>



Parameters

Name	Unit
Working width	500 mm
Width	600 mm
Height	350 mm
Number of sickle	2 pcs
Drivegear	Hydraulic system
Attachment	Universal .
Other	Hydraulic intercept

Description

An excellent example of Aardenbug's versatility is the disc mower, a hydraulically propelled side arm that can be mounted on any machine with three bolts. The disc mower is able to go around fruit trees and poles, so it can mow the area between the trees. It requires 30-50 litres of oil per minute, 1 pair of hydraulic couplings and a so-called oil drain connection. The vertical rotating shaft is equipped with 2 blades protected from shocks by a metal flange. The overall width of the implement is 60 cm and the working width is 50 cm. The mower is able to follow uneven ground thanks to an ingenious solution: the parallelepiped hitch with screw.

It is recommended for use with a grinder, but can also be combined with the Trimmer frame, a multifunctional frame that can easily be attached to a forklift, tractor or even a loader. This frame also has the advantage of hydraulic side tilt, which allows the position of the mower to be easily changed in relation to the wire. Our customers usually install the detachable disc mower on row crops for row cultivation, but it is also excellent for mowing under electric fences, or close to fences and next to them.

The deflection function is automatic, controlled by a bumper bar at the front of the machine. When the bar encounters a resistance, usually a fruit tree or pole, the roller retracts the mower and when this resistance is removed the roller pushes the mower back into position. Hydraulic deflection requires another pair of hydraulic connections.