

FDR-200

Rotary tiller with hydraulic sideshift 200 cm

Item no.: B15-5451

Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/fdr-200-rotary-tiller-with-hydraulic-sideshift-200-cm>

**Parameters**

Name	Value
Working width	2000 mm
Minimum HP	70 hp
Number of discs on rotor	8 pcs
Number of rotavator blade	48 pcs
Weight	570 kg
Maximum HP	80 HP
Working depth	250 mm

Description

The FDR model is a high performance reinforced rotary tiller for all types of plantations and nurseries.

It is especially recommended for tractors of all models and powers from 35 to 80 HP.

It has 6 knives per disc and a transmission rotor shaft by means of pinions and chain in oil bath of 1 1/2", allowing a good work, with low power consumption. The working depth is 24 cm and the FDR model has the conventional safety systems of cardan to the power take-off with disc clutch. The agricultural milling machine model FDR, also has a lateral displacement system by means of a hydraulic cylinder that allows it to move the machine from the tractor wheel. Likewise, the system of coupling to the tractor is by means of hitch and three-point linkage plates for the tractor and therefore allows a wide range of anchoring measures to the different tractors.

The rear hinged door is manufactured in the FDR milling machine model in different formats.

The FDR milling machine is also manufactured in different widths from 1.40 meters to 2.00 meters.

The agricultural machine meets the working objectives for seedbed preparation, field weeding and soil preparation for sowing bases.

The FDR model is equipped with a special turret and a spindle drive system (hydraulic as an option) that allows work to be shifted with respect to the centre of the tractor.

Options:

- 1 1/2" chain drive in oil bath.
- One speed
- Cardan shaft and hitch pins.
- Reinforced chassis.
- Working depth 25 cm. Adjustable by skids.