

Belafer FFL-110**Rotary tiller 110 cm****Company seat**

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/b15-5442>

**Parameters**

Name	Unit
Working width	1100 mm
Working depth	12 mm
Minimum HP	22 hp
Number of discs on rotor	5 pcs
Number of rotavator blade	30 pcs
Weight	230 kg
Maximum HP	25 HP

Description

The FFL model is a high performance Lightweight rotary tiller, ideal for all types of plantations and nurseries, especially recommended for tractors from 10 to 55 HP.

It has 6 knives per disc and a rotor shaft with transmission by means of pinions and chain in oil bath of 1 1/4", with a working depth of 12 cm. One of the main characteristics of the FFL model is that its design allows good work with low power consumption. At a safety level, the FFL model has a cardan shaft system at the power take-off with a disc clutch.

The FFL has a system of coupling to the tractor by means of coupling plates with movable flanges, which allows a wide range of anchoring measures to the different tractors.

As far as customisation is concerned, FFL milling machines are manufactured in different widths from 0.80 metres to 1.50 metres.

In short, the FFL model is a light rotary tiller that is very versatile and that meets the working objectives for sowing, field weeding and land preparation for seedbeds, and that thanks to its design can be used on a wide range of tractors.

FFL Fixed Light Rotary Tiller

Series adapted for small tractors and work in reduced spaces, greenhouses and green areas. Series of great resistance and reliability.

Standard:

- 1 1/4" chain drive in oil bath.
- One-speed group.
- 6 blades per disc.
- Cardan shaft and hitch pins.
- Direction of rotation right.
- Working depth up to 14 cm. Adjustable by skids.
- Rotor speed 190 RPM.