

HMM-170

Hydraulic front mulcher 170cm

Item no.: J33-10237



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/hmm-170-hydraulic-front-mulcher-170cm>



Parameters

Name	Value
Weight	355 kg
Working width	1700 mm
Total width	1900 mm

Description

The Jansen HMM-170 hydraulic mulching mower is characterized by its particularly durable design. It excels as a mulching mower, tractor mower, etc. and is particularly suited for maintaining pastures, meadows, lawns and green spaces with grass, bushes, and smaller branches. It is very versatile thanks to its hydraulic drive.

Jansen's flail mower HMM-170 is designed with a hydraulic drive in the front attachment and typically used for agricultural use, on private properties, or by municipalities and communities.

With its Euro-style mounting bracket, the Jansen HMM-170 mulching mower is not only suited for tractors. Thanks to the hydraulic drive, the mower can be used universally and therefore also be attached to farm loaders, mini excavators, municipal vehicles, and much more.

Weighing approx. 400 g, the 28 specially hampered blades crush the cutting material to minimum size. Even very high grass and bushy or straw-like materials are no problem for this mower! The spiral arrangement of the mallets also provides an ideal suction effect for an improved distribution of force and quiet operation.

Thanks to its even drive shaft load, the double spiral shaft drive provides particularly quiet operation and lasting durability with significantly reduced effort. Even very high grass, and bushy or straw-like materials are no problem for this mower!

In addition, the mulching mower is also equipped with a heavy trailing roller. The cutting height can be adjusted via the skids attached to the side.

Oscillating, suspended, galvanized slats on the front of the mower prevent the ejection of stones, etc. The 3 covered belts secure additional overloads.

The connected vehicle should have a minimum output of 20 HP and must be equipped with a hydraulic circuit.

Technical information:

Drive: Hydraulic system (3 belts powered by a hydraulic system)

Working width: 1,700 mm

Total width: 1,900 mm

Exterior height: 400 mm

Power requirements: min. 55 l/min, 180 bar

Required oil pressure: 180 - 200 bar

Required oil amount: 55 - 65 l/min.

Hammer blades: approx. 400 g, 28 pieces

Euro-style front-end loader mounting bracket

2 impellers on the front exterior

Double spiral drive shaft (dia. 110 mm)

height-adjustable trailing roller (dia. 100 mm)

Front guard: cantilever galvanized slats

Packaging: Wooden box

Package Dimensions: 194x85x78 cm (LxWxH)

Weight: approx. 355 kg

Weight including packaging: approx. 406 kg