

Jansen HRW-15

Lumber trailer



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/j33-10403>



Parameters

Name	Unit
Tank capacity	5 L
Weight	620 kg
Dimensions	3900x1350x2000 mm
Hydraulic oil	9 L

Description

The lumber trailer is equipped with hydraulic all-wheel drive, which can be switched on and off, to ensure that it can be moved with ease even on very uneven terrain. The all-wheel drive can be switched on electrically via a magnetic valve.

The lumber trailer is hydraulically supported.

The loading crane, included as part of delivery, has a swivel range of approx. 180 degrees and a maximum reach of 3.2m. At the maximum jib length of 3.2m, the crane has a lifting capacity of 200kg. At 2.0m the crane can lift 300kg. The crane has a hydraulic grab which can rotate 360 degrees.

The total loading capacity of the lumber trailer is 1,500kg.

The hydraulic unit also comes as part of delivery and is powered using a 6.5 HP 4-stroke petrol engine.

The cable winch is powered hydraulically and can be operated via remote control, which makes lifting cut trunks much easier, as you can stand directly next to the trunk and operate the winch using the remote control. The steel cable of the winch has a length of 20 metres.

The trailer can be moved easily using the tow bar. Many of our customers tow the trailer with an ATV, quad or small tractor. These allow flexibility on narrow paths. The trailer is not permitted for transport on public roads. The trailer is not permitted for transport on public roads.

The forwarding trailer will be completely assembled and filled by us before it is handed over to the customer. This applies exclusively to pick-up on site in 49824 Emlichheim.

Technical specifications:

4-stroke OHV engine, 6.5 HP

Fuel type: petrol

Tank capacity: 5 l

Starter: Recoil starter

Weight: 620 kg without fluids

Load capacity: max. 1,500 kg

Crane swivel range: approx. 180 degrees

Crane reach: max. 3.20 m

Lifting power of crane: 300 kg at a jib length of 2 m

Width of grab: 750 mm



Cable winch: hydraulic, 20 m steel cable

Trailer coupling and towing mechanism included

Tyres: 22x11x10

Operating pressure of hydraulic oil: 190 bar

Switchable, hydraulic all-wheel drive

Support: hydraulic, 2-fold

Assembled dimensions: approx. 390x135x200 cm (LxWxH)

Amount of engine oil: approx: 0.8 l (10W40 or 15W40)

Hydraulic oil tank capacity: approx. 9 l (HLP46)

Dimensions of packaging: approx. 300x80x170 cm (LxWxH)

Weight including packaging: approx. 678 kg