

Jansen HRW-15pro

Lumber trailer, galvanized



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/j33-10404>



Parameters

Name	Unit
Tank capacity	4 L
Weight	630 kg
Dimensions	3900x1350x2000 mm
Hydraulic oil	7.5 L

Description

Major variations from our standard model HRW-15:
galvanized edition

hydraulic retractable support feet, hiding in the frame

The lumber trailer is equipped with hydraulic all-wheel drive, which can be switched on and off, to ensure that it can be moved with ease even on very uneven terrain. The all-wheel drive can be switched on electrically via a magnetic valve.

The lumber trailer is additionally hydraulically supported. The support feet disappear in the frame instead of being folded down.

The loading crane, included as part of delivery, has a swivel range of approx. 180 degrees and a maximum reach of 3.5m. At the maximum jib length of 3.5m, the crane has a lifting capacity of 200kg. The crane has a hydraulic grab which can rotate 360 degrees.

The total loading capacity of the lumber trailer is 1,500kg.

The hydraulic unit also comes as part of delivery and is powered using a 6.5 HP 4-stroke petrol engine with electric starter.

The cable winch is powered hydraulically and can be operated via remote control, which makes lifting cut trunks much easier, as you can stand directly next to the trunk and operate the winch using the remote control. The steel cable of the winch has a length of 18 metres with a diameter of 5 mm.

The trailer can be moved easily using the tow bar. Many of our customers tow the trailer with an ATV (or quad or small tractor), as you are also very flexible on narrow paths. The trailer is not permitted for transport on public roads.

The forwarding trailer will be completely assembled and filled by us before it is handed over to the customer. This applies exclusively to pick-up on site in 49824 Emlichheim.

Technical specifications:

4-stroke OHV engine, 6.5 HP with electric starter

Fuel type: petrol

Tank capacity: 4 l

fully galvanized frame

Starter: Recoil and electric starter

Weight: 630 kg without fluids

Weight including packaging: 656 kg

Load capacity: max. 1,500 kg

Crane swivel range: approx. 180 degrees

Crane reach: max. 3.50 m

Tyres: 22x11x10

Lifting power of hydraulic grab: 200 kg

Width of grab: 750 mm

Cable winch: hydraulic, 18 m steel cable (diameter of 5 mm)

Trailer coupling and towing mechanism included

Operating pressure of hydraulic oil: 160 bar

Switchable, hydraulic all-wheel drive

Support: hydraulic, 2-fold

Assembled dimensions: 390x135x200 cm (LxWxH)

Dimensions of packaging: 366x126x89 cm (LxWxH)

Amount of engine oil: approx. 0.8 l (10W40 or 15W40)

Hydraulic oil tank capacity: approx. 7.5 l (HLP46)