

Belafer MAC-3-6-H

120 cm Hydraulic driven front mounted arm flail mower (6m arm)



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/b15-1738>



Parameters

Name	Unit
Working width	1200 mm
Weight	1010 kg
Number of Y knife	36 pcs
Hydraulic pressure	250 bar
Oil flow	60-100 l/min

Description

MAC Hydraulic arm-mulcher to be coupled on backhoes with ranges from 5 m to 6 m and telescopic up to 7 m. The front coupling system is adjusted on the blade support by means of a structure according to the backhoe model. Handling by means of proportional distributor with joystick and perfect adjustment of all handling functions by means of a cable to the backhoe cab. Lateral positioning with all movements and ranges at distances of between 5 and 7 metres. Perfect staggering of movements, as well as efficient work where required. 1 or 1.20 m mower heads with knife, hammer or interchangeable cutting system. The machine has the necessary counterweights in case they are required by the carrier.

- Arm lengths 5-6 m and telescopic at 7m.
- Front hook on shovel.
- Flow splitting valve.
- Electric controls.
- Mechanical support legs.
- Direct reversible motor.
- Anti-projection rear skirt.
- Full positioner roller.
- Automatic safety valve.
- Oil cooler.
- absorbed power 30 hp