



Belafer MAC-3-7-TEL

120 cm Hydraulic driven front mounted arm flail mower (7m telescopic arm)



Parameters

Name	Unit
Working width	1200 mm
Weight	1210 kg
Number of Y knife	36 pcs
Hydraulic pressure	250 bar
Oil flow	60-100 l/min

Description

MAC Hydraulic arm-mulcher to be coupled on backhoes with ranges from 5 m to 6 m and telescopic up to 7 m. The front coupling system is adjusted on the blade support by means of a structure according to the backhoe model. Handling by means of proportional distributor with joystick and perfect adjustment of all handling functions by means of a cable to the backhoe cab. Lateral positioning with all movements and ranges at distances of between 5 and 7 metres. Perfect staggering of movements, as well as efficient work where required. 1 or 1.20 m mower heads with knife, hammer or interchangeable cutting system. The machine has the necessary counterweights in case they are required by the carrier.

-Arm lengths 5-6 m and telescopic at 7m.

-Front hook on shovel.

-Flow splitting valve.

-Electric controls.

-Mechanical support legs.

-Direct reversible motor.

-Anti-projection rear skirt.

-Full positioner roller.

-Automatic safety valve.

-Oil cooler.

-absorbed power 30 hp

Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/b15-1739>

