

Tecnovict Mod.216

Double row chemical desuckering machine



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/t21-2014>



Parameters

Name	Unit
Weight	278 kg
Working height	300-900 mm
Side move	600 mm
Vertical shift	800 mm

Description

The double row chemical desuckering machine mod.216 is suitable for desuckering vineyards with espalier training systems. It carries out this task by applying a liquid containing a drying solution to the lower part of the plant, below the fruit-bearing branches, thus wetting the suckers and drying them out completely. It is applied to the front of the tractor. Recommended for 1,80 – 3,20 m. width rows vineyards. suitable to overcome poles of 2.50 max, box 40 cm height. (Other sizes on request)

- Frame with hydraulic movement vertical (80 cm.) and horizontal (60 cm.)
- Telescopic frame to fit the height of the bridge to the canopy height
- Adjustable Head Width (from 74 to 82 cm.)
- Isolation top with brush system to bristle end in two layers separated by PVC sheet upper doors brush holder in compass openable stainless steel for internal inspection
- Frame with safety device against accidental bumps
- Guides invitation poles and automatically extendable strains with springy return nozzle columns flexibly mounted
- Kit to use the machine as an only weed spraying hydraulic hoses with quick couplings for connection to the distributor of the tractor