

## Tecnovict Mod.280-165

### Trimmer machine



#### Company seat

Agrohof Kft.  
6064 Tiszaug, Bokros tanya 16.

#### Sales

+34 667 954 677  
info@agrohof.com

<https://agrohof.com/sku/t21-2021>



### Parameters

Name	Unit
Weight	260 kg
Oil flow	28-35 l/min
Side move	800 mm
Vertical shift	600 mm
Topping width	600-700 mm
Cutting bars vertical height	1650 mm

### Description

The maximum efficiency and speed of work with a simple machine to safely trim both sides of the row at the right of the tractor. The high-speed blades system is the most performant from the point of view of the operational capacity in hours per hectares and is assisted in this by the strong chassis at inverted U. It works with the hydraulic flow from the tractor, but is suggested the use with independent hydraulic central at the rear of the tractor to avoid heating. The strong chassis is also protected from the possibility of collision with poles hidden by vegetation by using a safety device that allows the rotation of the whole horizontal part of the chassis around a pin placed at the top of the vertical column and its return in position once raised the head and overcome the obstacle.

- Horizontal hydraulic movement 600 mm.
- Vertical hydraulic movement 800 mm.
- Floating head with shock absorbers
- Hydraulic tilt +/- 20° as optional
- Electro-hydraulic controls with joystick
- Safety device for impact against the ground with gas spring return
- Garaging stand