



## MCMs PHW240T

Rear mounted forklift (max. 700 kg lifting capacity)



### Company seat

Agrohof Kft.  
6064 Tiszaug, Bokros tanya 16.

### Sales

+34 667 954 677  
info@agrohof.com

<https://agrohof.com/sku/m16-1622>



### Parameters

Name	Unit
Weight	520 kg
Lifting	700 kg

### Description

Hydraulic forklift truck-mounted loader is used to load and unload goods placed in boxes, pallets and containers and to transport these goods over short distances. The transport can take place on unpaved land. Loader is a machine suspended on a three-point linkage (three-point linkage), designed for tractors of 0.6 ÷ 0.9T class. It is mounted on the front axle support of a tractor with external hydraulic output (single acting cylinder). The maximum lifting height is 2.4 m and the maximum loader lifting capacity is 700 kg. Hydraulic forklift loader consists of two basic units: lifting mechanism and loader frame. The lifting mechanism consists of: outer guide, inner guide, fork plate, pick-up fork, plunger cylinder and lifting line. The frame consists of: frame steel structure, brackets (left and right) and a reciprocating piston cylinder. Elements for mounting the hydraulic system are supplied separately. To tilt the guide, the piston cylinder is mounted horizontally in the lower part of the frame. The operating principle of all loader types is the same. They only differ in the way they are attached to the tractor's front axle bracket, the connection of the distributor to the external hydraulic system and the length of the hydraulic line.

- hidraulic shift
- frame made of double ironworks profile
- adjustable fork spacing
- possibility of shift assembly
- folding forks
- the loader can be adapted to most models of popular tractors (case, McCormick)
- mounted the rear three-point linkage