

Belafer RE-120

Rotary tiller 120 cm



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/b15-5446>



Parameters

Name	Unit
Working width	1200 mm
Working depth	12 mm
Minimum HP	35 hp
Number of discs on rotor	5 pcs
Number of rotavator blade	30 pcs
Weight	320 kg
Maximum HP	40 HP

Description

Semi-reinforced fixed rotary tiller with high performance for all types of plantations and nurseries. It is specially recommended for tractors of all models and powers from 30 to 60 hp.

It has 6 knives per disc and a rotor shaft with transmission by means of pinions and chain in oil bath of 1 1/2", allowing a good work with low power consumption. The working depth is 12 cm and the RE model has the conventional safety systems of cardan to the power take-off with disc clutch.

Likewise, the coupling system to the tractor is by means of three-point linkage plates for the tractor and therefore allows a wide range of anchoring measures to the different tractors. The rear hinged door is manufactured in the model of RE milling machine in different formats.

The RE is also manufactured in different widths from 1.00 meters to 1.80 meters.

The agricultural machine fulfills the work objectives for the preparation of sowings, weeding of fields and preparation of land for sowing beds.

Fixed semi-reinforced rotary tiller RE

The RE series is used by semi-professionals in fruit farms, wine growers and horticulturalists for its high performance and reliability even in difficult terrain. Option: Can be ordered with a lateral displacement system by means of a hydraulic cylinder that allows it to move the machine from the tractor wheel.

Standrd:

- 1 1/2" chain drive in oil bath.
- Single-speed group.
- 6 blades per disc.
- Cardan shaft and hitch pins.
- Direction of rotation right.
- Working depth up to 12 cm. Adjustable by skids.
- Rotor speed 220 RPM.