

RotaryTillerDF6-500

Rotary Tiller 500 cm

Item no.: F41-4821



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/rotarytillerdf6-500-rotary-tiller-500-cm>



Parameters

Name	Value
Company	Forigo

Description

Machinery composed by a tilling rotor, complete with blades rotating in the tractor forwarding direction and a rear hood for soil containing. The working depth can be adjusted by lateral skids, wheels, rollers or rear bed former hoods. Our rotary tillers achieve very high-level of soil tilling, even in presence of weed, cultural residues and very tough fields. Therefore, they are suitable for primary as for secondary soil preparation. The horizontal tilling rotor, available in various diameters, can fit different types of blades, in relation to the soil natural conditions and working procedures. The series is composed by fixed, movable - by mechanical or hydraulic system - and folding machines up to 700 cm working width. Universal 3 point linkage Cat. 2 & 3, Tractor linkage swinging arms, Single speed gearbox 1000 rpm PTO, Special FORIGO exclusive double transmission driven by 6 gears in oil bath, Opposite side inner transmissions in oil bath, Front tilling rotor Ø600 mm, Removable flanged rotors with top blades towards the outside, 6x speed "C" blades per flange, Wearing steel protection counter-flanges, Rear adjustable hoods, Hydraulic system for opening and refolding, Hydraulic locking system for transport position, Working depth adjustable by crank handles, 280 cm wide during transport, Rear lights bar, Lateral cardan shaft with automatic torque limiter SC type, Central standard cardan shaft (1"3/8 Z=6 tractor side yoke)