

RotaryTillerF3SA-200

Rotary Tiller 200 cm

Item no.: F41-4800



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/rotarytillerf3sa-200-rotary-tiller-200-cm>



Parameters

Name	Value
Company	Forigo

Description

Machinery composed by a tilling rotor, complete with blades rotating in the tractor forwarding direction and a rear hood for soil containing. The working depth can be adjusted by lateral skids, wheels, rollers or rear bed former hoods. Our rotary tillers achieve very high-level of soil tilling, even in presence of weed, cultural residues and very tough fields. Therefore, they are suitable for primary as for secondary soil preparation. The horizontal tilling rotor, available in various diameters, can fit different types of blades, in relation to the soil natural conditions and working procedures. The series is composed by fixed, movable – by mechanical or hydraulic system – and folding machines up to 700 cm working width. Universal 3 point linkage Cat. 2, Automatic hydraulic side shift by sensor, Shift operation exclusion device, Automatic hydraulic plant for machine side shifting, Single speed gearbox 540 rpm PTO, Lateral transmission driven by gears, Opposite side transmission in oil bath, Front dual metal face seals in oil bath on rotors, Removable flanged rotor with top blades towards the inside, 6x speed "C" blades per flange, Adjustable rear hood by chain, Pair of height adjustable front skids, Cardan shaft with shear bolt torque limiter SB type (1"3/8 Z=6 tractor side yoke)