

## Yanmar SA424-R (demo)

### Tractor (ROPS) 26 HP



#### Company seat

Agrohof Kft.  
6064 Tiszaug, Bokros tanya 16.

#### Sales

+34 667 954 677  
info@agrohof.com

<https://agrohof.com/sku/y95-12489>



### Parameters

Name	Unit
Cylinders	3 pcs
Torque	67.8 Nm
Generator	12V/55 A
Battery	12V/54 Ah
Turning circle	2600 mm
Max speed forward	23.3 km/h
PTO Power	14.5 kW
Rear PTO Speed	540 RPM
Mid. PTO Speed	2000 RPM
Front PTO speed	1000 RPM
Fuel Tank volume	23 L
Hydraulic oil tank capacity	15 L
Capacity hydro Pump	28.3 l/min
Hydraulic pump implements	15.1 l/min
Hydraulic pressure	167 bar
Hydraulic connection / pair	2 .
3 point lift capacity	713 kg
Front 3 point lift capacity	530 kg
Length	2793 mm
Width	1436 mm
Ground clearance	260 mm
Height	1675 mm
Wheelbase	160 cm
Weight	846 kg

Name	Unit
Engine	3TNM72-DRE HP
Transmission	Hydrostatic 2 Range
Tractor Motor Power	18.9 KW
Tractor Power	26 HP
Engine size	1115 cm3

## Description

Lawn wheel set R4, Size: FT: 23x8.50-12 - RT: 36x13.50-15

Tooth weight bracket (without weights)

Tool box

- demo, tractor with roll over protective structure
- 3TNM72-DRE type, 26 hp, 3-cylinder, 1115 cm<sup>3</sup> Yanmar diesel engine
- Fuel tank: 23 l
- Torque: 67.8 NM
- Drive: Hydrostatic
- Transmission type: 2-speed hydro
- 2 speed ranges 500 m/h - 10 km/h, 0 - 20 km/h
- Brake: Multi-disc oil-immersed
- All-wheel drive: Mechanically switchable
- Power output on PTO shaft: 19 HP
- Rear PTO speed: 540 rpm
- Front (optional) PTO speed: 1000 rpm
- Middle (optional) PTO speed: 2000 rpm
- Hydraulic oil tank: 15.5 l
- Hydraulic power: 15.1 l/min and 167 Bar
- Remote hydraulic circuits: 2 pairs on the right side of the tractor
- Steering: Servo-assisted
- Rear three-point type: Cat.I linkage
- Three-point lifting capacity rear / front: 713 / 530 kg
- Dimensions (L x W x H): 2,793 x 1,436 x 1,675 mm
- Turning circle: 2,600 mm
- Ground clearance: 260 mm
- Weight: 846 kg
- Towing capacity for unbraked trailer: 700 kg
- Towing capacity for braked trailer: 1,600 kg
- Smooth and stepless gear changes from zero to maximum speed
- Programmable hand throttle in both 2 speed ranges