

StoneBurrierTG45-200

Stone Burier 600 cm

Item no.: F41-4938



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/stoneburriertg45-200-stone-burier-600-cm>



Parameters

Name	Value
Company	Forigo

Description

These machines process the soil and bury stones, clods, debris and cultural residues with great efficiency, even in difficult conditions and in not previously prepared fields. The inverted rotation of a special rotor (opposite to the forwarding direction) combined with a selector rake and a levelling bar cover the buried material with a fine and clean soil layer. Stone buriers simplify the seeding/transplanting operations of several vegetable- and special crops creating very well formed, stable and porous cultivation beds. This series is very large and it's composed by single, double, triple fixed and folding/foldable machine to suit every kind of job and tractor power. Universal 3 point linkage Cat. 2 & 3, Tractor linkage swinging arms, Single speed gearbox 1000 rpm PTO, Central standard cardan shaft (1"3/8 Z=6 tractor side yoke), Lateral cardan shaft with automatic torque limiter SC type, Central machine joint with automatic limiter SC, Pair of front discs adjustable in height and width on lateral machines, Pair of middle ploughshares adjustable in height and width, Swinging and side adjustable machines supports, Bases and joints for machines linkage, Pair of supporting rear wheels for central machine, Hydraulic system for opening and refolding, Hydraulic locking system for transport position, 225 cm wide during transport, Rear lights bar. 3x Independent Stone Buriers which can be used individually: Machines equipment: Universal 3 point linkage Cat. 2 & 3 Single speed gearbox, 540 rpm PTO Lateral transmission driven by chain in oil bath, Automatic chain stretcher, Opposite side transmission in oil bath, Front dual metal face seals in oil bath on rotors, Removable flanged rotor, Rotor fitting 6x spade blades per flange , Wearing steel protection counter-flanges, High resistance steel side pannel, Lateral transmission with cardan shaft, Rear double selector rake mounted on lateral springs, Working depth adjustable by crank handles.