

MCMs SZ-H-25-50**Rear mounted auger with hydraulic sideshift(with drillbit)****Company seat**

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/m16-1626>

**Parameters**

Name	Unit
Weight	200 kg

Description

The ground twig with hydraulic travel is a machine mounted on a three-point linkage (three-point linkage), designed to work with agricultural tractors of 0.6 ÷ 0.9T class. The drive is transmitted via the PTO shaft of the tractor. The drill is used to drill holes in the ground when planting fruit trees and bushes, etc. There is a possibility to drill deeper holes, which allows to use the device for setting up fence posts, rows, etc. The machine drills holes in the ground vertically up to 65 cm with a ø50 cm drill diameter and up to 100 cm deep with a ø25 cm drill diameter. By adjusting the speed of the roller (PTO) we can set the width of scattered soil when drilling holes. For the auger, it is recommended to use a power relay fight with a breakaway fuse or a 250 Nm friction clutch, e.g. LFMR C 40970. Thanks to the use of a hydraulic cylinder, the auger can be moved up to 80 cm in relation to the axis of the tractor, which enables drilling holes in an existing row of trees.

- possibility of drilling holes in two rows during one pass thanks to moving the drill using hidraulic cylinder
- two drills in the set 25/100 and 50/65 (diameter/length cm)
- verticality of the drill