

## Jansen TBF-125

Tractor Tiller rotary tiller, rear tiller, field tiller. 1.25 m



### Company seat

Agrohof Kft.  
6064 Tiszaug, Bokros tanya 16.

### Sales

+34 667 954 677  
info@agrohof.com

<https://agrohof.com/sku/j33-10322>



### Parameters

Name	Unit
Width	1250 mm
RPM	540 rpm
Weight	350 kg

### Description

Whether for agriculture or field work, vineyards, orchards or landscaping - the Jansen TBF-125 tractor rotary tiller is ideal for every kind of tilling project. The tiller has a specially strengthened angular gearbox and is characterised by its especially robust construction. The shaft is powered by the gear wheels in an oil bath. The rear safety flap with built-in levelling springs eliminates uneven areas in the tilled soil and ensures it is broken up finely.

EXTREMELY ROBUST. SAFE. EFFICIENT.

Our many years of experience in development and manufacturing have produced a machine that is particularly distinguished by its extremely robust construction and thus clearly stands out from the competition.

WHAT DO WE DO DIFFERENTLY?

Reasonable material thicknesses and no thin sheets

reinforced and robust three-point hanger

robust milling blades on solid rotor shaft

P.T.O included

TECHNICAL SPECIFICATIONS:

Milling width: approx. 125 cm

Tilling depth: max. 16 cm (depending on soil properties)

Tiller blades: 36 total

Tiller blades per flange: 6 pieces

P.T.O.: included

Rpm: 540

Rotor shaft drive: gear drive in oil bath

Mount: Three-point hitch Cat. I + Cat. II

Weight: approx. 350 kg

Dimensions: 143x95x100 cm (LxWxH)

Pkg. dimensions: 155x85x88 cm (LxWxH)

Weight including packaging: approx. 380 kg

Tractor: min. 20 HP

The working width is approx. 125 cm and the tilling depth up to 16 cm. Both can be regulated using the runners mounted on the side. The



heavy-duty tiller blades are mounted to the tough rotor shaft. The tiller is driven using the P.T.O., which comes as part of delivery, and is mounted to the three-point linkage of your tractor (Cat. I + Cat. II).

This tiller is ideal for compact and narrow track tractors. Your tractor should have at least 20 hp power.