

TBF-180

Tractor Tiller rotary tiller, rear tiller, field tiller. 1.80m

Item no.: J33-10323



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/tbf-180-tractor-tiller-rotary-tiller-rear-tiller-field-tiller-180m>



Parameters

Name	Value
Weight	440 kg
RPM	540 rpm
Tractor Power	min 40 HP

Description

Whether for agriculture or field work, vineyards, orchards or landscaping - the Jansen TBF-180 tractor rotary tiller is ideal for every kind of tilling project. The tiller has a specially strengthened angular gearbox and is characterised by its especially robust construction. The shaft is powered by the gear wheels in an oil bath. The rear safety flap with built-in levelling springs eliminates uneven areas in the tilled soil and ensures it is broken up finely.

The working width is approx. 180 cm and the tilling depth up to 16 cm. Both can be regulated using the runners mounted on the side. The 8 rows of heavy-duty tiller blades are mounted to the tough rotor shaft. The tiller is driven using the P.T.O., which comes as part of delivery, and is mounted to the three-point linkage of your tractor (Cat. II).

Your tractor should have at least 40 HP.

Technical specifications:

Tractor: min. 40 HP

Milling width: approx. 180 cm

Tilling depth: max. 16 cm (depending on soil properties)

Tiller blades: 48 total

Tiller blades per flange: 6 pieces

P.T.O.: included

Rpm: 540

Dimensions: 207x85x90 cm (LxWxH)

Weight: approx. 440 kg

Rotor shaft drive: gear drive in oil bath

Mount: Three-point hitch Cat. II

Packaging: Steel frame

Pkg. dimensions: approx. 208x90x90 cm (LxWxH)

Weight including packaging: approx. 467 kg