

TS-22

Log splitter, 22 tons, PTO driven, vertical

Item no.: J33-10387



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/ts-22-log-splitter-22-tons-pto-driven-vertical>



Parameters

Name	Value
Weight	310 kg
Dimensions	1300x670x2470 mm

Description

Here we can offer you one of our newest models of log splitters. This is a very heavy-duty and robust design. The weight of the splitter alone is 320 kg! The enormous splitting force of 22 tons is obtained by using a tractor (drive via P.T.O., not included in delivery).

This model has been manufactured according to the latest EU product safety norm EN 609:2017.

The built-on log lifter is very practical, even heavy trunks can be lifted with ease. The log lifter can be locked in the upper position when it is not required, and serves in this position as a second guard rail.

Using a basic spring mechanism, the device can be operated in 2 different modes:

The splitting wedge automatically returns up to the predetermined position (can be varied in increments using a lever) once the operating lever is released. This makes fast and effective working possible, as you don't have to return the wedge manually to the top. For this mode of operation, the spring must be taken out.

The splitting wedge remains in position upon release of the operating lever and only returns to the top when the operating lever is pushed up. The spring must be inserted for this function.

The log splitter is mounted on 2 wheels which entail that it can be moved by hand; you must be extra careful when doing so due to the weight, and it is advisable to only move the splitter with at least 2 persons. Alternatively, it can also be fitted to the 3-point hinge of a tractor. The cylinder can be lowered to a height of 1.88m without problem.

The log splitter works at 2 speeds: A fast speed for moving to the wood and a slower speed for the splitting process.

The devices are all very stable and offer enormous power. You will not be able to find a piece of wood which this splitter cannot handle.

Included in the delivery is a cross wedge. Within the European Union it is not allowed to use this cross wedge with the log splitter. According to the latest EU norm EN 609:2017 it is generally prohibited to use cross wedges or multiple splitting wedges on log splitters.

Using the cross wedge is done on one's own risk and responsibility.

Technical specifications:

Splitting force: max. 22 tons

Log lifter: included

4-way splitting wedge: included

Operating modes: 2

Limit of cylinder stroke: adjustable

Drive: P.T.O. (not included in delivery)

Weight: approx. 310 kg

max. log opening: 110 cm

Cylinder speed: 8 sec. forward

Cylinder speed: 10 sec. backward

Amount of hydraulic oil: Approx. 24L (HLP46)

Distance wedge to bottom: 20 cm

Diameter cylinder: 115 mm

Diameter piston rod: 60 mm

Dimensions: 130x67x247 cm (LxWxH)

Measurements of packaging: 94x68x200 cm (LxBxH)

Weight including packing: 320 kg