

TS-30 P.T.O & Electric

Log splitter, 30 tons combi (PTO + electric motor), vertical

Item no.: J33-10389



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

<https://agrohof.com/product/ts-30k-log-splitter-30-tons-combi-ptu-electric-motor-vertical>



Parameters

Name	Value
Weight	400 kg
Dimensions	1540x1140x2510 mm

Description

Here we can offer you one of the newest models of log splitters. This is a very heavy-duty and robust design. The weight of the splitter alone is 400 kg!

This model has been manufactured according to the latest EU product safety norm EN 609:2017.

The enormous splitting force of 30 tons is obtained through an electric motor (400V, 5.5 kW) or by using a tractor (drive via P.T.O., not included in delivery).

The splitter is therefore universal.

A phase inverter has been integrated into the connection socket for the power cable.

The built-on log lifter is very practical, even heavy trunks can be lifted with ease. The log lifter can be locked in the upper position when it is not required, and serves in this position as a second guard rail.

The cylinder can be lowered to a height of 1.99m without problem. The log splitter works at 2 speeds: A fast speed for moving to the wood and a slower speed for the splitting process.

Using a basic spring mechanism, the device can be operated in 2 different modes:

The splitting wedge automatically returns up to the predetermined position (can be varied in increments using a lever) once the operating lever is released. This makes fast and effective working possible, as you don't have to return the wedge manually to the top. For this mode of operation, the spring must be taken out.

The splitting wedge remains in position upon release of the operating lever and only returns to the top when the operating lever is pushed up. The spring must be inserted for this function.

Included in the delivery is a cross wedge. Within the European Union it is not allowed to use this cross wedge with the log splitter. According to the latest EU norm EN 609:2017 it is generally prohibited to use cross wedges or multiple splitting wedges on log splitters.

Using the cross wedge is done on one's own risk and responsibility.

Technical specifications:

400 Volt engine with 5.5 kW

Splitting force: max. 30 tons

Log lifter: included

4-way splitting wedge: included

Operating modes: 2

Limit of cylinder stroke: adjustable

Drive: Electric motor or P.T.O. (P.T.O. not included in delivery)

Weight: 400 kg

max. log opening: 110 cm

Cylinder Speed (PTO): max. 5,5 Sec. / 9,5 Sec.

Cylinder Speed (electric): max. 7,5 Sec. / 14,5 Sec.

Diameter cylinder: 138 mm

Diameter piston rod: 70 mm

Dimensions: 154x114x251 cm (LxWxH)

Measurements of packaging: 98x68x200 cm (LxBxH)

Weight incl. packaging: 405 kg

Amount of hydraulic oil: Approx. 30L (HLP46)