

Toscano TSCO-Power Harrow - Standard 250

Power harrow 250 cm



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/t89-6712>



Parameters

Name	Unit
Working width	2500 mm
Width	2600 mm
Number of hoes	20 pcs
Weight	1184 kg
Working depth	280 mm
Minimum HP	80 hp

Description

Power Harrow is a tillage machine with vertical blades that turns right and left continuously. It prepares seedbed; eliminates weed and plant residue; mixes fertilizer; creates water channels in deeper layers of the soil. It also minimizes stratification. Power harrow does not turnover the soil, keeps the moisture inside. Since the blades operates right and left, it does not hold any soil or mud. Vertical operation increases the water intake of the soil. It allows the plant roots to develop faster by preventing stratification deep in the soil. Specially adjusted blade alignment increases efficiency while reducing vibration. Seeding machine connection tool makes it possible for preparing the seedbed and sowing at the same time. STANDARD EQUIPMENT Universal 3-point CAT II Linkage 1 3/8" Z6 Spline PTO Protective Shaft Double Outlet PTO Gearbox with 540-750-1000 rpm provides 2500-3000: min:195 max:361 3500-4000: min:236 max:437 Rotor Speed 280mm length 12 mm thick High Quality Blades. Packer Roller with Sludge Separator Rotor Prevention System (Developed by Toscano; prevents hose, rope, wire etc. tangling) Anti-Jamming System (Prevents stone jamming between rotors) Rear Roller Pin Adjustment Adjustable Levelling Profile Mobile & Adjustable side covers Removable CE Safety Guards