

Toscano TSCO-ROTARY TILLER - FOLDING 520

Rotary Tiller Folding 520 cm



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/t89-6721>



Parameters

Name	Unit
Working width	5200 mm
Width	5600 mm
Road width	240 cm
Weight	3062 kg
Working depth	270 mm
Number of Rippers	3 pcs
Number of hoes	120 pcs
Minimum HP	300 hp

Description

Rotary Tiller or Rotavator is a tillage machine that mixes the soil from bottom to the surface with the help of horizontally rotating hoes. It is used for preparing seed bed; ventilating the soil; shredding and mixing the plant wastes and weeds in the soil. The roller ensures flatter soil surface while working. Tillage machine that fully crumbles the soil; it maximizes seeds touch to the soil. Since it turnovers the soil; it causes mixing the plant wastes into soil homogeneously. Special blade angles enable tilling with faster speed even on the hard clods. Rippers in front of the machine ensures easier tillage even in harder soils. STANDARD EQUIPMENT Universal 3-point CAT III or CAT IV linkage 1 3/8" Z21 Spline PTO Protective Shaft 1000 rpm gearbox speed provides 258 rotor speed 10 mm thick high quality blades Cage roller Hydraulic roller adjustment kit Transmission set with robust gears 3 front rigid shanks Removable CE safety guards 120-132 Blades; 6 blades per flange; 3 blades on side flanges.