

**Toscano TSCO-ROTARY TILLER - HEAVY DUTY 335****Rotary Tiller, heavy duty 335 cm****Company seat**

Agrohof Kft.  
6064 Tiszaug, Bokros tanya 16.

**Sales**

+34 667 954 677  
info@agrohof.com

<https://agrohof.com/sku/t89-6718>

**Parameters**

| Name              | Unit    |
|-------------------|---------|
| Working width     | 3350 mm |
| Width             | 3550 mm |
| Number of hoes    | 78 pcs  |
| Weight            | 1580 kg |
| Working depth     | 270 mm  |
| Number of Rippers | 6 pcs   |
| Minimum HP        | 160 hp  |

**Description**

Rotary Tiller or Rotavator is a tillage machine that mixes the soil from bottom to the surface with the help of horizontally rotating hoes. It is used for preparing seed bed; ventilating the soil; shredding and mixing the plant wastes and weeds in the soil. The roller ensures flatter soil surface while working. Tillage machine that fully crumbles the soil; it maximizes seeds touch to the soil. Since it turnovers the soil; it causes mixing the plant wastes into soil homogeneously. Special blade angles enable tilling with faster speed even on the hard clods. Rippers in front of the machine ensures easier tillage even in harder soils. STANDARD EQUIPMENT Universal 3-point CAT II Linkage 1 3/8" Z6 Spline PTO Protective Shaft 540-750-1000 rpm Gearbox provides min150-max325 Rotor Speed 8 mm thick high quality blades Cage Roller Roller Adjustment Kit Transmission Set with Robust Gears 6 Rippers Removable CE Safety Guards 78-84-90 blades; 6 blades per flange; 3 blades on side flanges.