

**Toscana TSCO-ROTARY TILLER - STONE / STALK BURIER 261**  
**ROTARY TILLER - STONE / STALK BURIER with packer roller 261 cm**

**Company seat**  
 Agrohof Kft.  
 6064 Tiszaug, Bokros tanya 16.

**Sales**  
 +34 667 954 677  
 info@agrohof.com

<https://agrohof.com/sku/t89-6723>



**Parameters**

Name	Unit
Working width	2610 mm
Width	2920 mm
Number of hoes	66 pcs
Weight	1655 kg
Working depth	250 mm
Minimum HP	120 hp

**Description**

Rotary tiller is a tillage machine that mixes the soil from bottom to the surface with the help of horizontally rotating hoes. Stoneburier rotary tiller is used for preparing seed beds on rocky/stony fields to burry the stones below 20 cm of field surface. Roller ensures flatter soil surface while working. Tillage machine that crumbles the soil so the seeds will find an easy way to grow. Mixes the plant wastes into soil homogeneously. Since the rotor turns backward, it crumbles the soil in the maximum level. Cleans the stones from field and prepares the soil for the sensitive seeds. STANDARD EQUIPMENT Universal 3-point CAT II Linkage 1 3/8" Z6 Spline PTO Protective Shaft 540-750-1000 rpm Gearbox Speed provides min208-max325 Rotor Speed 12mm thick High Quality Blades. Packer roller with Sludge Separator Hydraulic Roller Adjustment Kit Transmission Set with Robust Gears 54-66-72-78-84 Blades; 6 blades per flange.