

Toscano TSCO-ROTARY TILLER - STONE / STALK BURIER 284

ROTARY TILLER - STONE / STALK BURIER with packer roller 284 cm

Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/t89-6724>



Parameters

Name	Unit
Working width	2840 mm
Width	3150 mm
Number of hoes	72 pcs
Weight	1750 kg
Working depth	250 mm
Minimum HP	140 hp

Description

Rotary tiller is a tillage machine that mixes the soil from bottom to the surface with the help of horizontally rotating hoes. Stoneburier rotary tiller is used for preparing seed beds on rocky/stony fields to bury the stones below 20 cm of field surface. Roller ensures flatter soil surface while working. Tillage machine that crumbles the soil so the seeds will find an easy way to grow. Mixes the plant wastes into soil homogeneously. Since the rotor turns backward, it crumbles the soil in the maximum level. Cleans the stones from field and prepares the soil for the sensitive seeds. STANDARD EQUIPMENT Universal 3-point CAT II Linkage 1 3/8" Z6 Spline PTO Protective Shaft 540-750-1000 rpm Gearbox Speed provides min208-max325 Rotor Speed 12mm thick High Quality Blades. Packer roller with Sludge Separator Hydraulic Roller Adjustment Kit Transmission Set with Robust Gears 54-66-72-78-84 Blades; 6 blades per flange.