

## TSCO-ROTARY TILLER - STONE / STALK BURIER 342

ROTARY TILLER - STONE / STALK BURIER with packer roller 342 cm

Item no.: T89-6726



### Seller

Agrohof Kft.  
6064 Tiszaug, Bokros tanya 16.  
Tax number: 25366895-2-03  
EU VAT number: HU25366895

### Sales

+36 56 770 010  
info@agrohof.com

<https://agrohof.com/product/tSCO-rotary-tiller-stone-stalk-burier-342-rotary-tiller-stone-stalk-burier-with-packer-roller-342-cm>



### Parameters

| Name           | Value   |
|----------------|---------|
| Working width  | 3420 mm |
| Width          | 3760 mm |
| Number of hoes | 84 pcs  |
| Weight         | 2450 kg |
| Working depth  | 250 mm  |
| Minimum HP     | 200 hp  |

### Description

Rotary tiller is a tillage machine that mixes the soil from bottom to the surface with the help of horizontally rotating hoes. Stoneburier rotary tiller is used for preparing seed beds on rocky/stony fields to burry the stones below 20 cm of field surface. Roller ensures flatter soil surface while working.

Tillage machine that crumbles the soil so the seeds will find an easy way to grow.

Mixes the plant wastes into soil homogeneously.

Since the rotor turns backward, it crumbles the soil in the maximum level.

Cleans the stones from field and prepares the soil for the sensitive seeds.

#### STANDARD EQUIPMENT

Universal 3-point CAT II Linkage

1 3/8" Z6 Spline PTO Protective Shaft

540-750-1000 rpm Gearbox Speed provides min208-max325 Rotor Speed

12mm thick High Quality Blades.

Packer roller with Sludge Separator

Hydraulic Roller Adjustment Kit

Transmission Set with Robust Gears

54-66-72-78-84 Blades; 6 blades per flange.