

## Toscano TSCO-SUBSOILER STANDARD - WELDED 2330-5 (demo NEW)

### Welded Rigid-Frame Subsoiler 233 cm



#### Company seat

Agrohof Kft.  
6064 Tiszaug, Bokros tanya 16.

#### Sales

+34 667 954 677  
info@agrohof.com

<https://agrohof.com/sku/t89-12252>



#### Parameters

| Name              | Unit      |
|-------------------|-----------|
| Working width     | 2330 mm   |
| Number of Rippers | 5 pcs     |
| Weight            | 915 kg    |
| Minimum HP        | 90-110 hp |
| Required power    | 66-81 KW  |
| Working depth     | 450 mm    |

#### Description

The primary tillage equipment subsoiler; rips the deep soil layers. It tills the soil without turning over in parallel to the driving direction. It can be used in hard and cloddy soils. It breaks the impermeable soil layer that prevents water penetration and root growth. The star roller behind the equipment levels the loosened soil surface.

- Does not overturn the soil; the soil keeps its moisture.
- Breaks the deep soil layers; supports vertical root growth for the plants.
- Provides fuel efficiency compared to classical tillage equipment.
- Ventilates the soil and creates water reservoir below the surface.
- With different roller options, offers the opportunity to prepare cloddy soils in a single pass.

For the original product: <https://agrohof.com/product/tsco-subsoiler-standard-welded-2330-5-welded-rigid-frame-subsoiler-233-cm>