AgroHof.com

TSCO-SUBSOILER STANDARD - WELDED 2330-5

Welded Rigid-Frame Subsoiler 233 cm

Item no.: T89-12197



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

https://agrohof.com/product/tsco-subsoiler-standard-welded-2330-5-welded-rigid-frame-subsoiler-233-cm

Parameters

Name	Value
Working width	2330 mm
Number of Rippers	5 pcs
Weight	915 kg
Minimum HP	90-110 hp
Required power	66-81 KW
Working depth	450 mm

Description

The primary tillage equipment subsoiler; rips the deep soil layers. It tills the soil without turning over in parallel to the driving direction. It can be used in hard and cloddy soils. It breaks the impermeable soil layer that prevents water penetration and root growth. The star roller behind the equipment levels the loosened soil surface.

- Does not overturn the soil; the soil keeps its moisture.
- Breaks the deep soil layers; supports vertical root growth for the plants.
- Provides fuel efficiency compared to classical tillage equipment.
- Ventilates the soil and creates water reservoir below the surface.
- With different roller options, offers the opportunity to prepare cloddy soils in a single pass.