AgroHof.com

U227-1

Power harrow Orion, 3.0 m, 12 rotors

Item no.: B07-0576



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

https://agrohof.com/product/u227-1-3-m-power-harrow-12-pcs-sickle

Parameters

Name	Value
Drivegear	tractor PTO
Working width	3000 mm
Working depth	200 mm
Number of knives	24 pcs
Weight	1270 – 1695 kg
Required power	90 KW
Minimum HP	122 hp

Description

Power harrows Orion are used for cultivation of soil after plowing and for sowing on mulch. The three-point suspension linkage is supported on a large width and ensures optimum power transfer. Movable arms with lower catches catenary category II and III provide optimal alignment with uneven terrain between the tractor and the suspended machine. Side deflectors have a double action as a cover against the threat and as a side stop for the treated soil and lumps. The side deflectors ensure uniformity of the field treatment and prevent the formation of mounds on the combination of one and the other pass. In the working position, the deflector must always be in contact with the surface of the field, so as not to damage it and limit its operation. It should be recessed at about 10 mm. The working depth (20 cm) is determined by positioning the rear roller. The power harrow is equipped with PTO shaft, leveling board, and hydraulic coupler (two hydraulic cylinders) as a standard.

Rollers: tubular Ø385 / string toothed Ø320 / packer Ø465 / rubber Ø500 mm. **Standard equipment:** PTO shaft, levelling board, hydraulic roller adjustment (2 cylinders).