

Jansen UKF-105

Reverse rotation tiller tractor tiller, pulverising roller, 1.05m



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/j33-10325>



Parameters

Name	Unit
Tractor Power	min 25 HP
RPM	540 rpm
Weight	308 kg

Description

Whether for agriculture or field work, vineyards, tree farms, orchards or landscaping - the Jansen UKF-105 reverse rotation tractor tiller is an indispensable tool in landscaping and agriculture and ideal for compact and narrow track tractors. The impressive power and innovative functions set new standards in soil and seedbed preparation. The working width is approx. 105 cm and the tilling depth approx. 16 cm. The tiller is driven using the P.T.O., which comes as part of delivery, and is mounted to the three-point linkage of your tractor (Cat. I and Cat. II). Your tractor should have at least 25 HP.

EXTREMELY ROBUST. SAFE. EFFICIENT.

Many years of experience in development and manufacturing have culminated in this tractor tiller, a machine that stands out particularly due to its robust construction and clearly differentiates itself from the competition.

WHAT DO WE DO DIFFERENTLY?

solid material thicknesses, no thin sheets

reinforced, robust three-point hanger

roller with extra strong mesh and material thicknesses

robust tilling blades on a solid rotor shaft

P.T.O. included

TECHNICAL DATA:

Tilling width: approx. 105 cm

Tilling depth: approx. 16 cm

Tiller blades: 20 total

Tiller blades per flange: 4 blades

P.T.O.: included

RPM: 540

Rotor shaft drive: Drive chain in oil bath

Mount: Cat. I + Cat. II

Weight: approx. 308 kg

Installed dimensions: approx. 140x130x100 cm (LxWxH)

Pkg. dimensions: approx. 133x100x95 cm (LxWxH)

Weight including packaging: approx. 360 kg



Tractor power: min. 25 HP

PULVERISING ROLLER FOR A PERFECT SEEDBED

One of the special features of the Jansen UKF-105 is the built-in pulverising roller. This roller ensures a top quality soil structure and pulverised seedbed, ideal conditions for sowing. The reverse direction tilling shaft throws stones and larger plant waste against the very tough digits, separating them from the soil. The result: optimal conditions for your plants to grow.

REVERSE ROTATION FOR OPTIMAL RESULTS

The Jansen UKF-105 reverse rotation tractor tiller is equipped with a tilling shaft which turns opposite to the direction of travel. This ensures the soil is worked thoroughly and pulverised for the seedbed. Resulting in even, high-quality soil conditions for your plants.

HIGH-RESISTANCE TILLING BLADES

The tilling blades on the Jansen UKF-105 are made from forged steel, developed specifically for lasting performance and extreme durability. No matter the challenge, with this tiller you are well equipped to achieve reliable results.