AgroHof.com

VMA-240

Flail mower 240cm

Item no.: J33-10262



Seller

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.
Tax number: 25366895-2-03
EU VAT number: HU25366895

Sales

+36 56 770 010
info@agrohof.com

https://agrohof.com/product/vma-240-flail-mower-240cm

Parameters

Name	Value
Mowing width	2320 mm
Weight	775 kg
RPM	540 rpm

Description

The especially robust construction of the mulch mower VMA-240 makes it stand out. It has a special reinforced angular gearbox and is outstanding in its operation. This flail mower with it´s professional quality is designed for commercial purposes.
The flail mower has a mowing width of 232 cm and is driven using a P.T.O, included as part of the delivery.
Due to the hydraulic lateral traverse function the mower can be moved to both left and right. For this function you need a hydraulic control circuit on your tractor, as the mower unit has a double-action hydraulic cylinder for this purpose.The cutting height can be set with the top controller and the runners mounted on the side. The VMA-240 mulching mower additionally has a trailing roller and a freewheel gearbox. The suspended chains at the front of the mower unit prevent stones escaping. Due to the open rear bonnet the mower even can be used to chop straw. Moreover it facilitates maintance work.
The 22 specially hardened, 1.2 kg hammer blades, arranged on a double spiral drive shaft, shred clippings to a minimum size. Even very high grass, bushy or straw-like clippings are no problem for this mower!The mower unit is hung using the three point linkage of your tractor (from Cat. II, with slight adaptation also Cat. I). Your tractor should have at least 80 HP.
Due to the Due to the open rear bonnet maintenance work or changing hammer blades will be facilitated. Please be informed that the bonnet have to be closed while operating.
Technical specifications:
Mowing width: 2320 mm
Hydraulic side-shift
Weight: 775 kg
P.T.O: Included in delivery
Drive belt: 5 pieces
drive shaft Ø: 160 mm
trailing roller Ø: 145 mm
Rpm: 540
Mounting: Three point hitch of Cat. II
Tractor: min. 80 HP
Packaging: wooden box
Dimensions of packaging: 2680x9600x970mm (L x W x H)
Weight including packaging: approx. 821 kg