

Jansen VMA-240

Flail mower 240cm



Company seat

Agrohof Kft.
6064 Tiszaug, Bokros tanya 16.

Sales

+34 667 954 677
info@agrohof.com

<https://agrohof.com/sku/j33-10262>



Parameters

Name	Unit
Mowing width	2320 mm
Weight	775 kg
RPM	540 rpm

Description

The especially robust construction of the mulch mower VMA-240 makes it stand out. It has a special reinforced angular gearbox and is outstanding in its operation. This flail mower with its professional quality is designed for commercial purposes.

The flail mower has a mowing width of 232 cm and is driven using a P.T.O, included as part of the delivery.

Due to the hydraulic lateral traverse function the mower can be moved to both left and right. For this function you need a hydraulic control circuit on your tractor, as the mower unit has a double-action hydraulic cylinder for this purpose. The cutting height can be set with the top controller and the runners mounted on the side. The VMA-240 mulching mower additionally has a trailing roller and a freewheel gearbox. The suspended chains at the front of the mower unit prevent stones escaping. Due to the open rear bonnet the mower even can be used to chop straw. Moreover it facilitates maintenance work.

The 22 specially hardened, 1.2 kg hammer blades, arranged on a double spiral drive shaft, shred clippings to a minimum size. Even very high grass, bushy or straw-like clippings are no problem for this mower! The mower unit is hung using the three point linkage of your tractor (from Cat. II, with slight adaptation also Cat. I). Your tractor should have at least 80 HP.

Due to the open rear bonnet maintenance work or changing hammer blades will be facilitated. Please be informed that the bonnet have to be closed while operating.

Technical specifications:

Mowing width: 2320 mm

Hydraulic side-shift

Weight: 775 kg

P.T.O: Included in delivery

Drive belt: 5 pieces

drive shaft Ø: 160 mm

trailing roller Ø: 145 mm

Rpm: 540

Mounting: Three point hitch of Cat. II

Tractor: min. 80 HP

Packaging: wooden box

Dimensions of packaging: 2680x9600x970mm (L x W x H)

Weight including packaging: approx. 821 kg